# ift-Nachweis



Result

Classification of thermoplastic wood adhesives for non-structural applications according to EN 204:2016-08



# **Durability classes: D 3**

Average adhesion strength - storage sequence 1 = 11.1 N/mm<sup>2</sup> Average adhesion strength - storage sequence 3 = 2.7 N/mm<sup>2</sup> Average adhesion strength - storage sequence 4 = 13.0 N/mm<sup>2</sup>

ift ROSENHEIM

Basis *)
 EN 204:2016-08
*) and corresponding national versions e.g. DIN EN)
Test report: 17-002777-PR03 PB- K15-09-de-01

## Instructions for use

The results obtained can be used as evidence in accordance with the above basis.

### Validity

There is no time limit. When using this document the upto-dateness of above basis and the conformity of the product have to be observed.

The data and results given relate solely to the tested/described specimen. This test/evaluation does not allow any statement to be made on further characteristics of the present structure regarding performance and quality.

#### Notes on publication

The ift-Guidance Sheet "Conditions and Guidance for the Use of ift Test Documents" applies.

ift Rosenheim 18.10.2017

M

#### Stefan Hehn, Dipl.-Ing. (FH) Deputy Head of Testing Department Laboratory for Material Testing

Section A.

Andreas Seebauer Operating Testing Officer Material Testing

Identity-Check



www.ift-rosenheim.de/ift-geprueft ID: 56D-A7BF9

Contact Phone: +49 8031 261-0 Fax: +49 8031 261-290 www.ift-rosenheim.de

Testing and Calibration – EN ISO/IEC 17025 Inspection – EN ISO/IEC 17020 Product Certification – EN ISO/IEC 17065 Certification of Management Systems – EN ISO/IEC 17021



**DAkkS** Deutsche Akkreditierungsstelle D-PL-11349-01-00